Double Barrel Grain Mover



www.grainhandler.com Toll Free Number: 800-260-1745



Grain Handler's Double Barrel Grain

Mover is a versatile chain conveyor that utilizes galvanized tube housing to gently convey a wide range of grain or grain products horizontally, or at angles of up to 60 degrees.

You can move grain efficiently and at high capacities while using less horsepower and causing less product damage than traditional conveying systems.

The unique UHMW paddle keeps grain flowing evenly from inlet to discharge, taking the place of traditional auger flighting.

This may be used individually or as part of our complete loop system.

- Pump spacer saddles are a bolt together design making it easier to modify lengths in the field.
 - Tube housing is galvanized 12 gage steel ensuring longevity and reducing maintenance.
 - Motors can be flipped to the bottom making it ideal for bin unloads and other applications.



 Ability to be head or tail driven.

- 1/2" Ultra High Molecular Weight (UHMW)
 paddles with a double backing and 3/8" cold
 rolled paddle back to ensure longevity.
- 81xHH chain on all sizes



Grain Handler, USA, Inc. is an industry leading manufacturer of Grain Dryers and Grain Handling equipment with installations on farms and grain elevators in the USA, Canada, Mexico, Australia, the Ukraine and China. Founded in 1986, the company leaders have decades of direct experience with farming, grain elevator operations and manufacturing.

The guiding principles of the company are to provide high quality, efficient, and economical products designed to suit the individual customer's needs.

8 "	Double	Barrel G	arain Mo	over / Ca	pacity:	4,000 B	PH / Ch	ain Spe	ed: 305	FPM		
8" Tube, 0 Degree Incline												
*Length	15'	20'	30'	40'	50'	55'	60'	70'	80'	90' - 120'	130' - 180'	
Horse Power	3.0	3.0	5	5	5	7.5	7.5	7.5	7.5	10	15	
8" Tube, 15 Degree Incline												
*Length	15'	20'	30'	40'	50'	55'	60'	70'	80'	90'	100'	
Horse Power	5.0	5.0	7.5	7.5	10	10	10	15	15	15	15	
8" Tube, 30 Degree Incline												
*Length	15'	20'	30'	40'	50'	55'	60'	70'	80'	90'	100'	
Horse Power	5.0	5.0	7.5	7.5	10	10	15	15	15	20	20	
8" Tube, 45 Degree Incline												
*Length	15'	20'	30'	40'	50'	55'	60'	70'	80'	90'	100'	
Horse Power	5.0	7.5	10	15	15	15	20	20	25	25	30	
8" Tube, 60 Degree Incline												
*Length	15'	20'	30'	40'	50'	55'	60'	70'	80'	90'	100'	
Horse Power	7.5	7.5	10	15	15	20	20	20	25	30	30	

10 " Double Barrel Grain Mover / Capacity: 6,000 BPH / Chain Speed: 325 FPM												
10" Tube, 0 Degree Incline												
*Length	15'	20'	30'	40'	50′	55'	60'	70'	80'	90′	100′	
Horse Power	3.0	5.0	5	7.5	7.5	7.5	7.5	10	10	15	15	
10" Tube, 15 Degree Incline												
*Length	15'	20'	30'	40'	50′	55'	60′	70'	80'	90′	100′	
Horse Power	5.0	5.0	7.5	7.5	10	10	15	15	15	20	20	
10" Tube, 30 Degree Incline												
*Length	15'	20'	30'	40'	50′	55'	60'	70'	80'	90'	100′	
Horse Power	5.0	7.5	10	15	15	15	20	20	25	25	30	
10" Tube, 45 Degree Incline												
*Length	15'	20'	30'	40'	50′	55'	60′	70'	80'	90′	100′	
Horse Power	7.5	7.5	15	15	20	20	25	25	30	40	40	
10" Tube, 60 Degree Incline												
*Length	15'	20'	30'	40′	50′	55'	60'	70'	80'	90′	100′	
Horse Power	10	10	15	20	25	25	30	30	40	40	40	
* Lengths are configurable												

Grain Handler Locations

Authorized Dealer

21785 Hamburg Ave. 1012 St. Charles Ave. Lakeville, MN 55044 St. Charles, MN 55972 Phone: 612-722-1085 Phone: 507-932-5492 Fax: 612-722-2642 Fax: 507-932-5492

www.grainhandler.com